



Rated current:	40A/ring
Number of contact:	2 contact
Rated voltage:	0-1000VAC/VDC
Operating speed:	0~ 4000 rpm

"WE RESERVE ALL RIGHTS IN CONNECTION WITH THIS DOCUMENT AND IN THE SUBJECT MATTER REPRESENTED THEREIN. THE RECIPIENT HEREBY ACKNOWLEDGES THESE RIGHTS AND SHALL NOT, WITHOUT OUR PRIOR PERMISSION IN WRITING, DISCLOSE OR DIVULGE THIS DOCUMENT IN WHOLE OR IN PART TO THE THIRD PARTIES OR USE IT FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT WAS DELIVERED TO RECIPIENT."

ANGULAR TOLERANCE: $\pm 0,5^\circ$	CUSTOMER:		Slip Ring Outline Drawing		
TOLERANCE:			APPLICATION:	Contact Ring With 2 Poles	
0,5 - 6 $\pm 0,1$	PROJECTION:	ARTICLE NO:		Designer: BHI	Date: 15.08.2022
>6 - 30 $\pm 0,2$					
>30 - 120 $\pm 0,3$					
>120 - 400 $\pm 0,5$					
>400 - 1000 $\pm 0,8$					
>1000 - 2000 $\pm 1,2$					
>2000 - 4000 $\pm 2,0$	<table border="1"> <tr> <td>Drawing No: 20001</td> <td>Rev:1</td> </tr> </table>	Drawing No: 20001	Rev:1		
Drawing No: 20001	Rev:1				