



Technical Specifications	
Circuits	42 Circuits - 42x20A
Rating Voltage	0-500Vac/Vdc
Dielectric Strength	≥500Vac@50Hz,60s
Insulation Resistance	≥300MΩ@300Vdc
Working Temperature	-20°C - +80°C
Working Humidity	≤60%RH
Working Speed	0-500 rpm
Contact Material	Gold to Gold
Housing Material	Aluminum Alloy
IP Grade	IP65

“WE RESERVE ALL RIGHTS IN CONNECTION WITH THIS DOCUMENT AND IN THE SUBJECT MATTER REPRESENTED THEREIN. THE RECIPIENT HEREBY ACKNOWLEDGES THESE RIGHTS AND SHALL NOT, WITHOUT OUR PRIOR PERMISSION IN WRITING, DISCLOSE OR DIVULGE THIS DOCUMENT IN WHOLE OR IN PART TO THE THIRD PARTIES OR USE IT FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT WAS DELIVERED TO RECIPIENT.”

ANGULAR TOLERANCE: ±0.5° TOLERANCE: >0.5 - 6 ± 0.1 >6 - 30 ± 0.2 >30 - 120 ± 0.3 >120 - 400 ± 0.5 >400 - 1000 ± 0.8 >1000 - 2000 ± 1.2 >2000 - 4000 ± 2.0	CUSTOMER:	Slip Ring Outline Drawing ZEN-X4 RSZQ-4220-S001	ARTICLE NO:		
	APPLICATION:		Designer: KHK	Date: 29.02.2024	Drawing No: 10063
	PROJECTION:				